

Operational Standards

OS - 1.12 | Site Signage

Revision:

C

Section:

1.0 - Site Setup & Housekeeping

Visual Aids

SAFETY SIGNAGE

WELFARE SIGNAGE

10 MPH
320 x 450mm



_____ pcs

BUCKET CHANGING
450 x 320mm



_____ pcs

CONCRETE WASHOUT
450 x 320mm



_____ pcs

CONSTRUCTION SITE
KEEP OUT
320 x 450mm



_____ pcs

CANTEEN
450 x 320mm



_____ pcs

DRYING ROOM
450 x 320mm



_____ pcs

EYE WASH STATION
320 x 450mm



_____ pcs

FIRE ASSEMBLY POINT
320 x 450mm



_____ pcs

DEEP EXCAVATION
450 x 320mm



_____ pcs

DEEP WATER
600 x 450mm



_____ pcs

DIESEL BOWSER
1280 x 450mm



_____ pcs

FIRE EXTINGUISHER
320 x 450mm



_____ pcs

FIRE POINT
320 x 450mm



_____ pcs

FIRST AID POINT
320 x 450mm



_____ pcs

FIRST AID TREATMENT
450 x 600mm



_____ pcs



Information

Objective	Application
● To highlight potential hazards and associated risks, through visual signage ● To provide information and instruction to site personnel and visitors ● Positively maintain and promote MIDA's brand	● Sites where MIDA are acting as Principal Contractor and Subcontractor
Site Setup Instructions	Operational Responsibilities
● Signs to be adequately secured to fences with cable ties ● Signs to be adequately secure to site containers (internal and external) ● Signage to be displayed in areas that are visible to the intended recipient i.e. Plant Operators ● Signage to be displayed in accordance with MIDA Operational Standards, Operational Instructions and RAMS	● Site signage is to be considered when identifying/reviewing temporary works - particularly wind loading effects ● Site signage should be inspected by the Site Manager weekly – old signage is to be removed if no longer relevant