

Operational Standards

OS - 1.7 | Material Storage Area

Revision:

A

Section:

1.0 - Site Setup & Housekeeping

Visual Aids



Information

Objective	Application
● To centralise and segregate material storage ● To store materials in good order, to achieve good standards of housekeeping ● To allow materials to be easily accessible and reduce double handling ● To protect materials from damage ● Positively promote MIDA’s brand	● Sites where MIDA are acting as Principal Contractor and Subcontractor
Site Setup Instructions	Operational Responsibilities
● Storage Area Surface – area to be stripped and levelled, size to be identified at pre-start ● Segregation – the material storage area is to be secured by blue Heras fencing, placed on feet and double clipped ● Access/egress points – to be controlled by double leafed access gate and separate pedestrian access gate ● External Signage – material storage area, groundwork only, no unauthorised access	● Materials to be placed on firm level ground and stacked neatly with no risk of falls ● Materials to be stacked no higher than two pallets, concrete pipes three high with chocks ● When offloading concrete pipes, pipes are to be lifted off from the collar end to prevent damage ● Pipe lifters are to be used when unloading pipes ● Operatives are not to climb onto the back of any delivery vehicle to off load, unless it has handrails ● Material storage area fencing to form part of the temporary works register ● Material storage areas are to be left secure when not being used/accessed ● Material storage areas to be inspected daily by the Site Manager