

Operational Standards

OS - 2.3 | Walkway - Pods

Revision:

B

Section:

2.0 - Segregation & Access

Visual Aids



Information

Objective	Application
● Provide a safe means of access for pedestrians during the initial set up of site and infrastructure works ● Provide a safe means of access for pedestrians in segregated groundworker only areas ● Provide clear communication and direction to pedestrians ● Positively promote MIDA's brand	● Sites where MIDA are acting as Principal Contractor and Subcontractor in groundworker only segregated areas
Site Setup Instructions	Operational Instructions
● Walkway Surface – area to be stripped, levelled & compacted; dependent on local conditions and contracted T&Cs, areas subjected to heavy pedestrian traffic can be constructed and compacted with 6F2 and plainings ● Barriers – interlinked red (& white, where applicable) heavy duty crowd barriers (usually x1) ● Access – red hooped gates to be located at access/crossing points ● Signage – groundworker only/no unauthorised access, pedestrian crossing point & thumbs up ● Location – Pods must be installed at intervals of no more than 30m and within clear line of site to the next red hooped access gate	● Pods are to be planned, updated on the TMP and reconfigured as per the programmed works (avoid plant crossing points where possible) ● Pod arrangements to form part of the temporary works register ● Signage to be inspected monthly and updated as required